

BUCKEYE LUBRICANTS #TLSG-2C SYNTHETIC COOLANT

Buckeye Lubricants #**TLSG-2C** was developed to prevent the leaching of cobalt on carbide grinding applications, but it is also suitable for machining and grinding applications.

Buckeye Lubricants #**TLSG-2C** provides significant increases in tool life on a variety of machining applications, using **carbide, HS steel** or **CBN tools**. It has proven to be particularly effective on materials that are difficult to machine such as **STAINLESS STEEL, INCONEL,** and **HASTALLOY**; as well as on abrasive metals including **CAST IRON** and **MALLEABLE IRON**.

#**TLSG-2C** is also suitable for most grinding operations. It's clarity enables the operator to see the work being done, while providing excellent finishes to the metal without loading the wheel.

TLSG-2C is a **LOW FOAMING** product making it suitable for high turbulence applications. It is also **NON-GUMMING** and has excellent corrosion resistance. In addition, its' cooling and lubricating properties make it an excellent product for creep feed grinding.



SAMPLES PROVIDED ON REQUEST

Buckeye Lubricants #**TLSG-2C** is a **SUPERIOR Synthetic Machining & Grinding Coolant** that is Suitable for **ALL Applications** but is **PARTICULARLY Effective on Carbide Grinding !!**



**Buckeye
Lubricants**

20801 Salisbury Rd.
Bedford, Ohio 44146
Phone: (216) 581-3600
FAX: (216) 581-2734

Email: sales@buckeyelubricants.com
Web: www.buckeyelubricants.com